

# O-RING

S E S

Dimension table - JIS B2401 ( P type )



JIS B2401 SIZE NO.	ATANDARD SIZE		GROOVE SIZE	
	I.D.	W	I.D.	O.D.
P-3	2.8	1.9	3	6
P-4	3.8	1.9	4	7
P-5	4.8	1.9	5	8
P-6	5.8	1.9	6	9
P-7	6.8	1.9	7	10
P-8	7.8	1.9	8	11
P-9	8.8	1.9	9	12
P-10	9.8	1.9	10	13
P-10A	9.8	2.4	10	14
P-11	10.8	2.4	11	15
P-11.2	11	2.4	11.2	15.2
P-12	11.8	2.4	12	16
P-12.5	12.3	2.4	12.5	16.5
P-14	13.8	2.4	14	18
P-15	14.8	2.4	15	19
P-16	15.8	2.4	16	20
P-18	17.8	2.4	18	22
P-20	19.8	2.4	20	24
P-21	20.8	2.4	21	25
P-22	21.8	2.4	22	26
P-22A	21.7	3.5	22	28
P-22.4	22.1	3.5	22.4	28.4
P-24	23.7	3.5	24	30
P-25	24.7	3.5	25	31
P25.5	25.2	3.5	25.5	31.5
P-26	25.7	3.5	26	32
P-28	27.7	3.5	28	34
P-29	28.7	3.5	29	35
P-29.5	29.2	3.5	29.5	35.5
P-30	29.7	3.5	30	36
P-31	30.7	3.5	31	37
P-31.5	31.2	3.5	31.5	37.5
P-32	31.7	3.5	32	38
P-34	33.7	3.5	34	40
P-35	34.7	3.5	35	41
P-35.5	35.2	3.5	35.5	41.5
P-36	35.7	3.5	36	42

JIS B2401 SIZE NO.	ATANDARD SIZE		GROOVE SIZE	
	I.D.	W	I.D.	O.D.
P-71	70.6	5.7	71	81
P-75	74.6	5.7	75	85
P-80	79.6	5.7	80	90
P-85	84.6	5.7	85	95
P-90	89.6	5.7	90	100
P-95	94.6	5.7	95	105
P-100	99.6	5.7	100	110
P-102	101.6	5.7	102	112
P-105	104.6	5.7	105	115
P-110	109.6	5.7	110	120
P-112	111.6	5.7	112	122
P-115	114.6	5.7	115	125
P-120	119.6	5.7	120	130
P-125	124.6	5.7	125	135
P-130	129.6	5.7	130	140
P-132	131.6	5.7	132	142
P-135	134.6	5.7	135	145
P-140	139.6	5.7	140	150
P-145	144.6	5.7	145	155
P-150	149.6	5.7	150	160
P-150A	149.5	8.4	150	165
P-155	154.5	8.4	155	170
P-160	159.5	8.4	160	175
P-165	164.5	8.4	165	180
P-170	169.5	8.4	170	185
P-175	174.5	8.4	175	190
P-180	179.5	8.4	180	195
P-185	184.5	8.4	185	200
P-190	189.5	8.4	190	205
P-195	194.5	8.4	195	210
P-200	199.5	8.4	200	215
P-205	204.5	8.4	205	220
P-210	208.5	8.4	210	225
P-215	209.5	8.4	215	230
P-220	214.5	8.4	220	235
P-225	219.5	8.4	225	240
P-230	224.5	8.4	230	245

O-RING

# O-RING

S E S

Dimension table - JIS B2401 ( P type )



JIS B2401 SIZE NO.	ATANDARD SIZE		GROOVE SIZE		JIS B2401 SIZE NO.	ATANDARD SIZE		GROOVE SIZE	
	I.D.	W	I.D.	O.D.		I.D.	W	I.D.	O.D.
P-38	37.7	3.5	38	44	P-235	229.5	8.4	235	250
P-39	38.7	3.5	39	45	P-240	234.5	8.4	240	255
P-40	39.7	3.5	40	46	P-245	239.5	8.4	245	260
P-41	40.7	3.5	41	47	P-250	244.5	8.4	250	265
P-42	41.7	3.5	42	48	P-255	249.5	8.4	255	270
P-44	43.7	3.5	44	50	P-260	254.5	8.4	260	275
P-45	44.7	3.5	45	51	P-265	259.5	8.4	265	280
P-46	45.7	3.5	46	52	P-270	265.5	8.4	270	285
P-48	47.7	3.5	48	54	P-275	269.5	8.4	275	290
P-49	48.7	3.5	49	55	P-280	274.5	8.4	280	295
P-50	49.7	3.5	50	56	P-285	279.5	8.4	285	300
P-48A	47.6	5.7	48	58	P-290	284.5	8.4	290	305
P-50A	49.6	5.7	50	60	P-295	294.5	8.4	295	310
P-52	51.6	5.7	52	62	P-300	299.5	8.4	300	315
P-53	52.6	5.7	53	63	P-315	314.5	8.4	315	330
P-55	54.6	5.7	55	65	P-320	319.5	8.4	320	335
P-56	55.6	5.7	56	66	P-335	334.5	8.4	335	350
P-58	57.6	5.7	58	68	P-340	339.5	8.4	340	355
P-60	59.6	5.7	60	70	P-355	354.5	8.4	355	370
P-62	61.6	5.7	62	72	P-360	359.5	8.4	360	375
P-63	62.6	5.7	63	73	P-375	374.5	8.4	375	390
P-65	64.6	5.7	65	75	P-385	384.5	8.4	385	400
P-67	66.6	5.7	67	77	P-400	399.5	8.4	400	415
P-70	69.6	5.7	70	80					

O-RING