

# O-RING

S E S

Dimension table - AS 568A




SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS		SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	A568	ID	W	ID		W	ID	W	ID
A-001	0.029	0.04	0.74	1.02	A-035	2.239	0.07	56.87	1.78
A-002	0.042	0.05	1.07	1.27	A-036	2.364	0.07	60.05	1.78
A-003	0.056	0.06	1.42	1.52	A-037	2.489	0.07	63.22	1.78
A-004	0.07	0.07	1.78	1.78	A-038	2.614	0.07	66.4	1.78
A-005	0.101	0.07	2.57	1.78	A-039	2.739	0.07	69.57	1.78
A-006	0.114	0.07	2.9	1.78	A-040	2.864	0.07	72.75	1.78
A-007	0.145	0.07	3.68	1.78	A-041	2.989	0.07	75.92	1.78
A-008	0.176	0.07	4.47	1.78	A-042	3.239	0.07	82.27	1.78
A-009	0.208	0.07	5.28	1.78	A-043	3.489	0.07	88.62	1.78
A-010	0.239	0.07	6.07	1.78	A-044	3.739	0.07	94.97	1.78
A-011	0.301	0.07	7.65	1.78	A-045	3.989	0.07	101.32	1.78
A-012	0.364	0.07	9.25	1.78	A-046	4.239	0.07	107.67	1.78
A-013	0.426	0.07	10.82	1.78	A-047	4.489	0.07	114.02	1.78
A-014	0.489	0.07	12.42	1.78	A-048	4.739	0.07	120.37	1.78
A-015	0.551	0.07	14	1.78	A-049	4.989	0.07	126.72	1.78
A-016	0.614	0.07	15.6	1.78	A-050	5.239	0.07	133.07	1.78
A-017	0.676	0.07	17.17	1.78	A-102	0.049	0.103	1.24	2.62
A-018	0.739	0.07	18.77	1.78	A-103	0.081	0.103	2.06	2.62
A-019	0.801	0.07	20.35	1.78	A-104	0.112	0.103	2.84	2.62
A-020	0.864	0.07	21.95	1.78	A-105	0.143	0.103	3.63	2.62
A-021	0.926	0.07	23.52	1.78	A-106	0.174	0.103	4.42	2.62
A-022	0.989	0.07	25.12	1.78	A-107	0.206	0.103	5.23	2.62
A-023	1.051	0.07	26.7	1.78	A-108	0.237	0.103	6.02	2.62
A-024	1.114	0.07	28.3	1.78	A-109	0.299	0.103	7.59	2.62
A-025	1.176	0.07	29.87	1.78	A-110	0.362	0.103	9.19	2.62
A-026	1.239	0.07	31.47	1.78	A-111	0.424	0.103	10.77	2.62
A-027	1.301	0.07	33.05	1.78	A-112	0.487	0.103	12.37	2.62
A-028	1.364	0.07	34.65	1.78	A-113	0.549	0.103	13.94	2.62
A-029	1.489	0.07	37.82	1.78	A-114	0.612	0.103	15.54	2.62
A-030	1.614	0.07	41	1.78	A-115	0.674	0.103	17.12	2.62
A-031	1.739	0.07	44.17	1.78	A-116	0.737	0.103	18.72	2.62
A-032	1.864	0.07	47.35	1.78	A-117	0.799	0.103	20.3	2.62
A-033	1.989	0.07	50.52	1.78	A-118	0.862	0.103	21.89	2.62
A-034	2.114	0.07	53.7	1.78	A-119	0.924	0.103	23.47	2.62

O-RING

# O-RING

S E S

Dimension table - AS 568A




SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS		SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	A568	ID	W	ID		W	A568	ID	W
A-120	0.987	0.103	25.07	2.62	A-281	14.984	0.139	380.59	3.53
A-121	1.049	0.103	26.64	2.62	A-282	15.955	0.139	405.26	3.53
A-249	4.859	0.139	123.42	3.53	A-283	16.955	0.139	430.66	3.53
A-250	4.984	0.139	126.59	3.53	A-157	4.487	0.103	113.97	2.62
A-251	5.109	0.139	129.77	3.53	A-158	4.737	0.103	120.32	2.62
A-252	5.234	0.139	132.94	3.53	A-159	4.987	0.103	126.67	2.62
A-253	5.359	0.139	136.12	3.53	A-160	5.237	0.103	133.02	2.62
A-254	5.484	0.139	139.29	3.53	A-161	5.487	0.103	139.37	2.62
A-255	5.609	0.139	142.47	3.53	A-162	5.737	0.103	145.72	2.62
A-256	5.734	0.139	145.64	3.53	A-163	5.987	0.103	152.07	2.62
A-257	5.859	0.139	148.82	3.53	A-164	6.237	0.103	158.42	2.62
A-258	5.984	0.139	151.99	3.53	A-165	6.487	0.103	164.77	2.62
A-259	6.234	0.139	158.34	3.53	A-166	6.737	0.103	171.12	2.62
A-260	6.484	0.139	164.69	3.53	A-167	6.987	0.103	177.47	2.62
A-261	6.734	0.139	171.04	3.53	A-168	7.237	0.103	183.82	2.62
A-262	6.984	0.139	177.39	3.53	A-169	7.487	0.103	190.17	2.62
A-263	7.234	0.139	183.74	3.53	A-170	7.737	0.103	196.52	2.62
A-264	7.484	0.139	190.09	3.53	A-171	7.987	0.103	202.87	2.62
A-265	7.734	0.139	196.44	3.53	A-172	8.237	0.103	209.22	2.62
A-266	7.984	0.139	202.79	3.53	A-173	8.487	0.103	215.57	2.62
A-267	8.234	0.139	209.14	3.53	A-174	8.737	0.103	221.92	2.62
A-268	8.484	0.139	215.49	3.53	A-175	8.987	0.103	228.27	2.62
A-269	8.784	0.139	221.84	3.53	A-176	9.237	0.103	234.62	2.62
A-270	8.984	0.139	228.19	3.53	A-177	9.487	0.103	240.97	2.62
A-271	9.234	0.139	234.54	3.53	A-178	9.737	0.103	247.32	2.62
A-272	9.484	0.139	240.89	3.53	A-201	0.171	0.139	4.34	3.53
A-273	9.734	0.139	247.24	3.53	A-202	0.234	0.139	5.94	3.53
A-274	9.984	0.139	253.59	3.53	A-203	0.296	0.139	7.52	3.53
A-275	10.484	0.139	266.29	3.53	A-204	0.359	0.139	9.12	3.53
A-276	10.984	0.139	278.99	3.53	A-205	0.421	0.139	10.69	3.53
A-277	11.484	0.139	291.69	3.53	A-206	0.484	0.139	12.29	3.53
A-278	11.984	0.139	304.39	3.53	A-207	0.546	0.139	13.87	3.53
A-279	12.984	0.139	329.79	3.53	A-208	0.609	0.139	15.47	3.53
A-280	13.984	0.139	355.19	3.53	A-209	0.671	0.139	17.04	3.53

O-RING

# O-RING

S E S

Dimension table - AS 568A



SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS		SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	A568	ID	W	ID		W	A568	ID	W
A-210	0.734	0.139	18.64	3.53	A-151	2.987	0.103	75.87	2.62
A-211	0.796	0.139	20.22	3.53	A-152	3.237	0.103	82.22	2.62
A-212	0.859	0.139	21.82	3.53	A-153	3.487	0.103	88.57	2.62
A-213	0.921	0.139	23.39	3.53	A-154	3.737	0.103	94.92	2.62
A-122	1.112	0.103	28.24	2.62	A-155	3.987	0.103	101.27	2.62
A-123	1.174	0.103	29.82	2.62	A-156	4.237	0.103	107.62	2.62
A-124	1.237	0.103	31.42	2.62	A-249	4.859	0.139	123.42	3.53
A-125	1.299	0.103	32.99	2.62	A-250	4.984	0.139	126.59	3.53
A-126	1.362	0.103	34.59	2.62	A-251	5.109	0.139	129.77	3.53
A-127	1.424	0.103	36.17	2.62	A-252	5.234	0.139	132.94	3.53
A-128	1.487	0.103	37.77	2.62	A-253	5.359	0.139	136.12	3.53
A-129	1.549	0.103	39.34	2.62	A-254	5.484	0.139	139.29	3.53
A-130	1.612	0.103	40.94	2.62	A-255	5.609	0.139	142.47	3.53
A-131	1.674	0.103	42.52	2.62	A-256	5.734	0.139	145.64	3.53
A-132	1.737	0.103	44.12	2.62	A-257	5.859	0.139	148.82	3.53
A-133	1.799	0.103	45.69	2.62	A-258	5.984	0.139	151.99	3.53
A-134	1.862	0.103	47.29	2.62	A-259	6.234	0.139	158.34	3.53
A-135	1.925	0.103	48.9	2.62	A-260	6.484	0.139	164.69	3.53
A-136	1.987	0.103	50.47	2.62	A-261	6.734	0.139	171.04	3.53
A-137	2.05	0.103	52.07	2.62	A-262	6.984	0.139	177.39	3.53
A-138	2.112	0.103	53.64	2.62	A-263	7.234	0.139	183.74	3.53
A-139	2.175	0.103	55.25	2.62	A-264	7.484	0.139	190.09	3.53
A-140	2.237	0.103	56.82	2.62	A-265	7.734	0.139	196.44	3.53
A-141	2.3	0.103	58.42	2.62	A-266	7.984	0.139	202.79	3.53
A-142	2.362	0.103	59.99	2.62	A-267	8.234	0.139	209.14	3.53
A-143	2.425	0.103	61.6	2.62	A-268	8.484	0.139	215.49	3.53
A-144	2.487	0.103	63.17	2.62	A-269	8.784	0.139	221.84	3.53
A-145	2.55	0.103	64.77	2.62	A-270	8.984	0.139	228.19	3.53
A-146	2.612	0.103	66.34	2.62	A-271	9.234	0.139	234.54	3.53
A-147	2.675	0.103	67.95	2.62	A-272	9.484	0.139	240.89	3.53
A-148	2.737	0.103	69.52	2.62	A-273	9.734	0.139	247.24	3.53
A-149	2.8	0.103	71.12	2.62	A-274	9.984	0.139	253.59	3.53
A-150	2.862	0.103	72.69	2.62	A-275	10.484	0.139	266.29	3.53

O-RING

# O-RING

S E S

Dimension table - AS 568A




SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS		SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	A568	ID	W	ID		W	A568	ID	W
A-276	10.984	0.139	278.99	3.53	A-333	2.475	0.21	62.87	5.33
A-277	11.484	0.139	291.69	3.53	A-334	2.6	0.21	66.04	5.33
A-278	11.984	0.139	304.39	3.53	A-335	2.725	0.21	69.22	5.33
A-279	12.984	0.139	329.79	3.53	A-336	2.85	0.21	72.39	5.33
A-280	13.984	0.139	355.19	3.53	A-337	2.975	0.21	75.57	5.33
A-281	14.984	0.139	380.59	3.53	A-338	3.1	0.21	78.74	5.33
A-282	15.955	0.139	405.26	3.53	A-339	3.225	0.21	81.92	5.33
A-283	16.955	0.139	430.66	3.53	A-340	3.35	0.21	85.09	5.33
A-284	17.955	0.139	456.06	3.53	A-341	3.475	0.21	88.27	5.33
A-309	0.412	0.21	10.46	5.33	A-342	3.6	0.21	91.44	5.33
A-310	0.475	0.21	12.07	5.33	A-343	3.725	0.21	94.62	5.33
A-311	0.537	0.21	13.64	5.33	A-344	3.85	0.21	97.79	5.33
A-312	0.6	0.21	15.24	5.33	A-345	3.975	0.21	100.97	5.33
A-313	0.662	0.21	16.81	5.33	A-346	4.1	0.21	104.14	5.33
A-314	0.725	0.21	18.42	5.33	A-347	4.225	0.21	107.32	5.33
A-315	0.787	0.21	19.99	5.33	A-348	4.35	0.21	110.49	5.33
A-316	0.85	0.21	21.59	5.33	A-349	4.475	0.21	113.67	5.33
A-317	0.912	0.21	23.16	5.33	A-350	4.6	0.21	116.84	5.33
A-318	0.975	0.21	24.77	5.33	A-351	4.725	0.21	120.02	5.33
A-319	1.037	0.21	26.34	5.33	A-352	4.85	0.21	123.19	5.33
A-320	1.1	0.21	27.94	5.33	A-353	4.975	0.21	126.37	5.33
A-321	1.162	0.21	29.51	5.33	A-354	5.1	0.21	129.54	5.33
A-322	1.225	0.21	31.12	5.33	A-355	5.225	0.21	132.72	5.33
A-323	1.287	0.21	32.69	5.33	A-356	5.35	0.21	135.89	5.33
A-324	1.35	0.21	34.29	5.33	A-357	5.475	0.21	139.07	5.33
A-325	1.475	0.21	37.47	5.33	A-358	5.6	0.21	142.24	5.33
A-326	1.6	0.21	40.64	5.33	A-359	5.725	0.21	145.42	5.33
A-327	1.725	0.21	43.82	5.33	A-360	5.85	0.21	148.59	5.33
A-328	1.85	0.21	46.99	5.33	A-361	5.975	0.21	151.77	5.33
A-329	1.975	0.21	50.17	5.33	A-362	6.225	0.21	158.12	5.33
A-330	2.1	0.21	53.34	5.33	A-363	6.475	0.21	164.47	5.33
A-331	2.225	0.21	56.52	5.33	A-364	6.725	0.21	170.82	5.33
A-332	2.35	0.21	59.69	5.33	A-365	6.975	0.21	177.17	5.33

O-RING

# O-RING

S E S

Dimension table - AS 568A




SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS		SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	A568	ID	W	ID		W	ID	W	ID
A-366	7.225	0.21	183.52	5.33	A-428	4.85	0.275	123.19	6.99
A-367	7.475	0.21	189.87	5.33	A-429	4.975	0.275	126.37	6.99
A-368	7.725	0.21	196.22	5.33	A-430	5.1	0.275	129.54	6.99
A-369	7.975	0.21	202.57	5.33	A-431	5.225	0.275	132.72	6.99
A-370	8.225	0.21	208.92	5.33	A-432	5.35	0.275	135.89	6.99
A-371	8.475	0.21	215.27	5.33	A-433	5.475	0.275	139.07	6.99
A-372	8.725	0.21	221.62	5.33	A-434	5.6	0.275	142.24	6.99
A-373	8.975	0.21	227.97	5.33	A-435	5.725	0.275	145.42	6.99
A-374	9.225	0.21	234.32	5.33	A-436	5.85	0.275	148.59	6.99
A-375	9.475	0.21	240.67	5.33	A-437	5.975	0.275	151.77	6.99
A-376	9.725	0.21	247.02	5.33	A-438	6.225	0.275	158.12	6.99
A-377	9.975	0.21	253.37	5.33	A-439	6.475	0.275	164.47	6.99
A-378	10.475	0.21	266.07	5.33	A-440	6.725	0.275	170.82	6.99
A-379	10.975	0.21	278.77	5.33	A-441	6.975	0.275	177.17	6.99
A-380	11.475	0.21	291.47	5.33	A-442	7.225	0.275	183.52	6.99
A-381	11.975	0.21	304.17	5.33	A-443	7.475	0.275	189.87	6.99
A-382	12.975	0.21	329.57	5.33	A-444	7.725	0.275	196.22	6.99
A-383	13.975	0.21	354.97	5.33	A-445	7.975	0.275	202.57	6.99
A-384	14.975	0.21	380.37	5.33	A-446	8.475	0.275	215.27	6.99
A-385	15.955	0.21	405.26	5.33	A-447	8.975	0.275	227.97	6.99
A-386	16.955	0.21	430.66	5.33	A-448	9.475	0.275	240.67	6.99
A-387	17.955	0.21	456.06	5.33	A-449	9.975	0.275	253.57	6.99
A-388	18.955	0.21	481.41	5.33	A-450	10.475	0.275	266.07	6.99
A-389	19.955	0.21	506.81	5.33	A-451	10.975	0.275	278.77	6.99
A-390	20.955	0.21	532.21	5.33	A-452	11.475	0.275	291.47	6.99
A-391	21.955	0.21	557.61	5.33	A-453	11.975	0.275	304.17	6.99
A-392	22.94	0.21	582.68	5.33	A-454	12.475	0.275	316.87	6.99
A-393	23.94	0.21	608.08	5.33	A-455	12.975	0.275	329.57	6.99
A-394	24.94	0.21	633.48	5.33	A-456	13.475	0.275	342.27	6.99
A-395	25.94	0.21	658.88	5.33	A-457	13.975	0.275	354.97	6.99
A-425	4.475	0.275	113.67	6.99	A-458	14.475	0.275	367.67	6.99
A-426	4.6	0.275	116.84	6.99	A-459	14.975	0.275	380.37	6.99
A-427	4.725	0.275	120.02	6.99	A-460	15.475	0.275	397.07	6.99

O-RING

# O-RING

S E S

Dimension table - AS 568A



SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	ID	W	ID	W
A-461	15.955	0.275	405.26	6.99
A-462	16.455	0.275	417.96	6.99
A-463	16.955	0.275	430.66	6.99
A-464	17.455	0.275	443.36	6.99
A-465	17.955	0.275	456.06	6.99
A-466	18.455	0.275	468.76	6.99
A-467	18.955	0.275	481.46	6.99
A-468	19.455	0.275	494.16	6.99
A-469	19.955	0.275	506.86	6.99
A-470	20.955	0.275	532.26	6.99
A-471	21.955	0.275	557.66	6.99
A-472	22.94	0.275	582.68	6.99
A-473	23.94	0.275	608.08	6.99
A-474	24.94	0.275	633.48	6.99
A-475	25.94	0.275	658.88	6.99


SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	ID	W	ID	W
A568				

O-RING

# O-RING

S E S

Dimension table - AS 568A



SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	ID	W	ID	W
A568				
M-901	0.185	0.056	4.7	1.42
M-902	0.239	0.064	6.07	1.63
M-903	0.301	0.064	7.65	1.63
M-904	0.351	0.072	8.92	1.83
M-905	0.414	0.072	10.52	1.83
M-906	0.468	0.078	11.89	1.98
M-907	0.53	0.082	13.46	2.08
M-908	0.644	0.087	16.36	2.21
M-909	0.706	0.097	17.93	2.46
M-910	0.755	0.097	19.18	2.46

SIZE Ref.	STANDARD SIZE INCHES		STANDARD SIZE MILLIMETERS	
	ID	W	ID	W
A568				
M-911	0.863	0.116	21.92	2.95
M-912	0.924	0.116	23.47	2.95
M-913	0.986	0.116	25.04	2.95
M-914	1.047	0.116	26.59	2.95
M-916	1.171	0.116	29.74	2.95
M-918	1.355	0.116	34.42	2.95
M-920	1.475	0.118	37.47	3
M-924	1.72	0.118	43.69	3
M-928	2.09	0.118	53.09	3
M-932	2.337	0.118	59.36	3

O-RING